

POLYAMIDE [66-GF30]

## Glass Filled Nylon - Rod [Ertalon 66-GF30] (Diameter Tolerances and Weights)

ROUND RODS				
Diameters [mm]	Tolerances <sup>[1]</sup> on the diameters [mm]	Ertalon® 66 – GF 30		
		Standard length per piece: [3000 mm <sup>[2]</sup> ]		
			[kg/pce <sup>[3]</sup> ]	
10	+0,1 +0,5		0,33	■
12			0,49	■
15			<b>0,75</b>	■
16	+ 0,2 +0,7		0,85	■
18			1,07	□
20			<b>1,31</b>	■
22			1,59	□
25	+0,2 +0,9		<b>2,04</b>	■
28			2,55	□
30			<b>2,91</b>	■
32			3,33	□
36	+0,2 +1,1		<b>4,20</b>	■
40			<b>5,16</b>	■
45			6,54	■
50	+0,3 +1,3		<b>8,04</b>	■
60			<b>11,58</b>	■
70	+0,3 +1,6		<b>15,66</b>	■
80	+0,4 +2,0		<b>20,52</b>	■
90	+0,5 +2,2		25,98	□
100	+0,6 +2,5		<b>32,10</b>	■
110	+0,7 +3,0		39,00	□
120			<b>46,50</b>	■
125	+0,8 +3,5		50,40	□
130			54,60	□
140	+0,9 +3,8		63,15	□
150	+1,0 +4,2		72,60	■
180	+1,2 +5,0		104,55	■
200	+1,3 +5,5		<b>128,85</b>	■

**Other standard length: [1000 mm<sup>[2]</sup>]**

<sup>[1]</sup>: tolerances according to EN 15860

<sup>[2]</sup>: tolerances on the length -0/+3 %

<sup>[3]</sup>: average production weight

- : **standard** item [generally available from stock; bulk quantities to be manufactured to order]
- : **semi-standard** item [generally not available from stock, minimum order quantity 1 piece]
- : **non-standard** item [generally not available from stock, manufactured to order and subject to special conditions; improved availability possible upon customer planning]