

POLYAMIDE [PA 66 + MOS<sub>2</sub>]

## Nylatron GS - Rod (Diameter Tolerances and Weights)

ROUND RODS			
Diameters [mm]	Tolerances <sup>[1]</sup> on the diameters [mm]	Nylatron® GS	
		Standard length per piece: [3000 mm <sup>[2]</sup> ] [kg/pce <sup>[3]</sup> ]	
6	+0,1 +0,4	0,11	□
8	+0,1 +0,5	0,19	□
10		<b>0,29</b>	■
12	+0,2 +0,7	<b>0,43</b>	■
15		0,66	□
16		<b>0,75</b>	■
18		<b>0,95</b>	■
20	+0,2 +0,9	<b>1,16</b>	■
22		1,41	□
25		<b>1,82</b>	■
28	+0,2 +1,1	2,27	□
30		<b>2,58</b>	■
32		<b>2,96</b>	■
35	+0,2 +1,3	<b>3,51</b>	■
40		<b>4,56</b>	■
45	+0,3 +1,3	<b>5,82</b>	■
50		<b>7,14</b>	■
Other standard length: [1000 mm <sup>[2]</sup> ]			

<sup>[1]</sup>: tolerances according to EN 15860

<sup>[2]</sup>: tolerances on the length -0/+3 %

<sup>[3]</sup>: average production weight

- : **standard** item [generally available from stock; bulk quantities to be manufactured to order]
- : **semi-standard** item [generally not available from stock, minimum order quantity 1 piece]
- : **non-standard** item [generally not available from stock, manufactured to order and subject to special conditions; improved availability possible upon customer planning]