

POLYAMIDE [PA 66 + MOS₂]

Nylatron GS - Tube (Tolerances, Weights and Availability)

TUBES				
Diameters [mm] O.D. x I.D.	Tolerances ^[1] on the diameters [mm]		Nylatron® GS	
	O.D.	I.D.	Standard length per piece: [3000 mm ^[2]] [kg/pce ^[3]]	
20 x 10			0,98	□
25 x 15	+0,4 +1,1	-0,4 -1,1	1,30	□
30 x 15			2,09	■
30 x 20			1,62	□
36 x 20			2,94	■
36 x 25	+0,6 +2,0	-0,6 -2,0	2,37	□
40 x 25			3,24	■
40 x 30			2,52	□
45 x 25			4,44	□
45 x 30			3,75	□
45 x 35			2,88	□
50 x 30			5,10	□
50 x 35			4,23	□
50 x 40			3,24	□
60 x 45			+0,8 +2,5	-0,8 -2,5
60 x 50	4,23	□		
65 x 50	6,18	□		
65 x 55	+0,8 +3,0	-0,8 -3,0	4,80	□
66 x 53			5,76	□
Other standard length: [1000 mm^[2]]				

For non-listed intermediate diameter, please consult us!

^[1]: tolerances according to EN 15860

^[2]: tolerance on the length -0/+3%

^[3]: average production weight

- : **standard** item [generally available from stock; bulk quantities to be manufactured to order]
- ▣ : **semi-standard** item [generally not available from stock, minimum order quantity 1 piece]
- : **non-standard** item [generally not available from stock, manufactured to order and subject to special conditions; improved availability possible upon customer planning]