

POLYAMIDE [PA 6 + SOLID LUBRICANTS]

Nylatron NSM - Rod (Diameter Tolerances and Weights)

ROUND RODS			
Diameters [mm]	Tolerances ^[1] on the diameters [mm]	Nylatron® NSM	
		Standard length per piece: [3000 mm ^[2]] [kg/pce ^[3]]	
50	+0,5 +1,5	7,08	□
56		8,85	□
60		10,29	□
65	+0,5 +1,8	11,95	□
70		13,80	□
75		15,95	□
80	+0,7 +2,3	18,10	□
85		20,55	□
90	+1,0 +2,7	23,00	□
95		25,60	□
100	+1,0 +2,9	28,35	□
110		34,35	□
120	+1,0 +3,3	40,95	□
125		44,25	□
130	+1,1 +3,8	48,00	□
140		55,50	□
150	+1,2 +4,1	63,75	□
	+1,3 +4,5		
Other standard length: [1000 mm ^[2]]			
[mm]	[mm]	Standard length per piece: [1000 mm ^[2]] [kg/pce ^[3]]	
160	+2,0 +7,0	24,60	□
170		27,65	□
180		30,95	□
190		34,40	□
200		38,00	□
210		42,40	□
220		46,40	□
225		48,50	□
230		50,60	□
240		55,00	□
250	+3,0 +9,0	59,55	□
260		64,30	□
270		69,25	□
275		71,75	□
280		74,35	□
290	79,60	□	
300	85,10	□	
325	+4,0 +11,0	100,50	□
350		116,10	□
375		133,00	□
400		150,90	□
425	+5,0 +13,0	171,20	□
450		191,50	□
475		212,90	□
500		235,40	□
Other standard length: [500 mm ^[2]]			

^[1]: tolerances according to EN 15860

^[2]: tolerances on the length -0/+3 %

^[3]: average production weight

- : **standard** item [generally available from stock; bulk quantities to be manufactured to order]
- ▣ : **semi-standard** item [generally not available from stock, minimum order quantity 1 piece]
- : **non-standard** item [generally not available from stock, manufactured to order and subject to special conditions; improved availability possible upon customer planning]