

POLYAMIDE [PA 66]

## Nylon 66 - Tube [Ertalon 66 SA] (Tolerances, Weights and Availability)

TUBES						
Diametres [mm] O.D. x I.D.	Tolerances <sup>[1]</sup> on the thicknesses [mm]			Standard length per piece: [3000 mm <sup>[2]</sup> ]	Ertalon® 66 SA natural	
	O.D.	I.D.			[kg/pce <sup>[3]</sup> ]	
20 x 10					0,94	□
20 x 15					0,62	□
22 x 10					1,18	□
25 x 12					1,46	□
25 x 15	+0,4 +1,1	-0,4 -1,1			1,25	□
25 x 18					1,00	□
28 x 12					1,91	□
30 x 15					2,03	□
30 x 20					1,58	□
32 x 15					2,51	□
32 x 20					2,07	□
32 x 25					1,49	□
36 x 17					3,12	□
36 x 25					2,27	□
40 x 20					3,69	□
40 x 25	+0,6 +2,0	-0,6 -2			3,12	□
40 x 30					2,40	□
45 x 20					—	—
45 x 25					4,32	□
45 x 30					3,60	□
45 x 35					2,75	□
50 x 20					—	—
50 x 25					—	—
50 x 30					4,92	□
50 x 40					3,09	□
55 x 25					—	—
55 x 35	+0,8 +2,5	-0,8 -2,5			5,73	□
60 x 30					—	—
60 x 40					6,36	□
65 x 40					—	—
70 x 30					—	—
70 x 40					—	—
70 x 50	+0,8 +3,0	-0,8 -3,0			7,80	□
75 x 30					—	—
75 x 50					—	—
80 x 40					—	—
80 x 50					—	—
80 x 60					9,09	□
90 x 40					—	—
90 x 50					—	—
90 x 60					—	—
100 x 40	+1,2 +3,6	-1,6 -5,0			—	—
100 x 50					—	—
100 x 60					—	—
100 x 80					12,54	□
Other standard length: [1000 mm <sup>[2]</sup> ]						

For non-listed intermediate diameter, please consult us!

<sup>[1]</sup>: tolerances according to EN 15860

<sup>[2]</sup>: tolerances on the length -0/+3 %

<sup>[3]</sup>: average production weight

■ : standard item [generally available from stock; bulk quantities to be manufactured to order]

☒ : semi-standard item [generally not available from stock, minimum order quantity 1 piece]

□ : non-standard item [generally not available from stock, manufactured to order and subject to special conditions;  
improved availability possible upon customer planning]