

## PTFE extruded rods

Extruded rods are supplied in standard length of 2m and 1m.

Available upon request:

- extruded rods in different diameters and length
- extruded rods of standard filled grades (with bigger dimensional tolerances)
- centreless-ground rods

De OD (mm)	Lunghezza Length (mm)	Peso* Weight* (g/m)
4	1000/ 2000	29
5	1000/ 2000	45
6	1000/ 2000	65
7	1000/ 2000	89
8	1000/ 2000	116
9	1000/ 2000	146
10	1000/ 2000	181
11	1000/ 2000	219
12	1000/ 2000	260
13	1000/ 2000	306
14	1000/ 2000	354
15	1000/ 2000	407
16	1000/ 2000	463
18	1000/ 2000	586
19	1000/ 2000	653
20	1000/ 2000	723
22	1000/ 2000	875
25	1000/ 2000	1130
28	1000/ 2000	1418
30	1000/ 2000	1627
32	1000/ 2000	1852
35	1000/ 2000	2215
40	1000/ 2000	2893
41	1000/ 2000	3039

De OD (mm)	Lunghezza Length (mm)	Peso* Weight* (g/m)
42	1000/ 2000	3189
45	1000/ 2000	3661
50	1000/ 2000	4520
55	1000/ 2000	5470
60	1000/ 2000	6509
65	1000/ 2000	7639
70	1000/ 2000	8860
75	1000/ 2000	10171
80	1000/ 2000	11572
85	1000/ 2000	13064
90	1000/ 2000	14646
100	1000/ 2000	18081
110	1000/ 2000	21878
120	1000/ 2000	26037
130	1000/ 2000	30557
150	1000/ 2000	40682

Tolleranze* - Tolerances*				
De OD (mm)		Lunghezza Length (mm)		
<=10	+0.6 -0	+2%	-0	
> 10	+6% -0	+2%	-0	

\* PTFE Vergine - Virgin PTFE

Weights are indicative and the indicated lengths are usually stocked.

Virgin PTFE  
ISO 13000-1 4.2.4  
TOLERANCES