

PTFE moulded rods

Available upon request:
Moulded rods in different diam. and lengths.
Rods moulded in standard filled grades in max.
lengths of 200 mm and diam. up to 150 mm, with
slightly larger tolerances.

De OD (mm)	Lunghezza Length (mm)	Peso* Weight* (g/mm)	Peso* Weight* (g/pcs)
50	300	4,52	1379
55	300	5,47	1668
60	300	6,51	1985
65	300	7,64	2330
70	300	8,86	2702
75	300	10,17	3102
80	300	11,57	3529
85	300	13,06	3984
90	300	14,65	4467
95	300	16,32	4977
100	300	18,08	5515
105	300	19,93	6080
110	300	21,88	6673
115	300	23,91	7293
120	300	26,04	7941
130	300	30,56	9320
140	300	35,44	10809
150	300	40,68	12408

De OD (mm)	Lunghezza Length (mm)	Peso* Weight* (g/mm)	Peso* Weight* (g/pcs)
160	300	46,29	14118
170	300	52,25	15938
180	300	58,58	17868
190	300	65,27	19908
200	300	72,32	22059
210	300	79,74	24320
220	300	87,51	26691
230	300	95,65	29173
250	300	113,01	34467
270	200	131,81	27021
290	300	152,06	46379
310	200	173,76	35621

Virgin PTFE
ISO 13000-1 4.2.4
TOLERANCES

Tolleranze* - Tolerances*	
De OD (mm)	Lunghezza Length (mm)
+6% -0	+10mm -0

* PTFE Vergine - Virgin PTFE

Weights are indicative and the indicated lengths are usually stocked.